

NEW!

Introducing the FireLock® Series 747M Zone Control Riser Module

available with Pressure Relief Option*

Designed for commercial, wet sprinkler systems, per NFPA 13 requirements. Features all required devices: waterflow switch and alarm connection, pressure gauge, alarm test with a range of available test orifices, drain connection and sight glass.

* Ask for Series 747MP for Pressure Relief Option

Features:

- Fully integrated one-piece cast ductile iron assembly
- ¼ turn shutoff and test device
- Grooved connections
- UL, ULC Listed and FM Approved
- Available with K5.6, K6.9, 8.0, 11.2, 16.8 test orifices
- Horizontal or Vertical installation
- Pressure rated up to 300 psi/ 2065 kPa
- Optional Pressure Relief version available

Benefits:

- **Easy system fit-up:** Grooved connections for rapid installation using Victaulic couplings.
- **Easier Handling:** 4" and 6" Riser Modules are significantly lighter in weight than competitive products
- **Easier Sprinkler System Testing:** ¼ turn shutoff and test device
- **Design Flexibility:** Multiple Orifice K-factors available to support a variety of system requirements.
- **Durability:** Cast one-piece ductile iron body provides a robust design that houses all operating components.

Available: December, 2007

See Product Publication 10.96

Visit www.victaulic.com or contact your local Victaulic representative for details.



Victaulic®
Piping. Systems. Solutions.